



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: John Eric Arnold et al.

For: AIRSPRING AND
AIRSPRING RETAINER

Serial No.: 10/009,696

Filed: November 6, 2001

Mail Stop Appeal Brief-Patents
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

) Confirmation No.: 1392
) Docket No. DN1999111USA
) Art Unit: 3683
) Examiner: Xuan Lan T Nguyen

) **BEFORE THE BOARD OF PATENT
APPEALS AND INTERFERENCES**

I hereby certify that this correspondence is
being deposited with the United States Postal
Service as first class mail in an envelope
addressed to: Mail Stop Appeal Brief-Patents,
Commissioner for Patents, P. O. Box 1450,
Alexandria, VA 22313-1450, on

June 25, 2007
Sandra Clancy
Sandra Clancy

**RESPONSE TO NOTIFICATION OF NON-COMPLIANT
APPEAL BRIEF (37 CFR 41.37)**

Dear Sir:

In response to the Notification of Non-Compliant Appeal Brief dated June 18, 2007, Appellants hereby submit their corrected "Summary of the Claimed Subject Matter" section which correctly describes the subject matter defined in each of the independent and dependent claims involved in the appeal. Applicants request that this corrected section be substituted for the incorrect "Summary of the Invention" section previously submitted.

Respectfully submitted,

June E. Rickey
June E. Rickey, Reg. No. 40,144
Attorney for Applicant

The Goodyear Tire & Rubber Company
Intellectual Property Law Department 823
1144 East Market Street
Akron, OH 44316-0001
Phone: 330-796-6366
Fax: 330-796-9018

Summary of the Claimed Subject Matter

Claims 1 and 16 are the independent claims pending in the application. Claims 2 – 9 depend from claim 1; claims 12, 14, and 17-20 depend from claim 16.

Independent Claim 1. Claim 1 is directed to an airspring 10 (Figure 1). The airspring 10 has a flexible cylindrical sleeve 14 secured at opposing ends (Figure 1; page 4, lines 3-7), and first and second retainers 12, 26 (page 4, line 4; page 4, lines 25-30). The sleeve is secured at a first end to one of the retainers 12 or 26 (page 4, lines 2-3, 8-9), and at the opposing end to other retainer 26 or 12 (page 6, lines 2-6). One of the retainers 26 has a bumper-contact surface 52 (page 5, lines 9-10) within the sleeve 14 for axial movement into the sleeve 14 (Figure 1). The bumper-contact surface 52 is formed as a part of the retainer (Figure 1; page 4, lines 26-27; page 5, lines 9-12) and it contacts the other retainer 12 when the airspring is collapsed, and absorbs and transmits forces generated from such contact (page 6, lines 7-10). The bumper contact surface 52 is centrally located on the surface of the retainer 26 which extends into the sleeve 14 during axial movement into the sleeve 14 (Figures 1 and 4; page 4, line 25 – page 5, line 8).

Independent Claim 16. Claim 16 is directed to an airspring 10 (Figure 1). The airspring 10 has a flexible cylindrical sleeve 14 secured at opposing ends (Figure 1; page 4, lines 3-7), a chamber 20 created by the secured sleeve 14 (page 4, lines 4-5), a piston 28 (page 4, lines 16-18), and first and second retainers 12, 26 (page 4, lines 4; page 4, lines 25-30). The sleeve is secured at a first end to one of the retainers 12 or 26 (page 4, lines 2-3, 8-9), and the opposing end of the sleeve 14 is secured between the piston 28 and the other retainer 26 or 12 (Figure 1; page 2-6). One of the retainers 26 has a centrally located axially outer surface 52 (page 5, lines 9-10). The axially outer surface 52 extends into the chamber 20 during axial movement, wherein the axially outer surface 52 of the retainer 26 contacts the other retainer 12 when the airspring is collapsed (page 6, lines 7-10).

Dependent Claim 12. Claim 12 is dependant on claims 16 and 17, and so in conjunction with claim 16, recites the air spring 10 of claim 16 wherein the retainer that extends into the chamber 20 has support ribs 34, 40, 42, 44, 48 (page 4, line 27 – page 5, 8; Figures 2-6) and there are more than two concentrically disposed ribs (page 4, lines 7-33; Figure 4).

Dependent Claim 20. Claim 20 is dependant on claim 16, and in conjunction with claim 16, further recites that the airspring 10 has no separately formed and applied bumper on either retainer (page 4, lines 26-27; Figure 1).